PRODUCT DATASHEET
LED VALUE Downlight 6.50 W 3000 K incurv

LED VALUE DOWNLIGHT INCURV | LED downlights



Areas of application

- Corridors
- Foyers
- Stairways
- Elevators

Product benefits

- Low flicker light thanks to special electronic control gear
- Direct connection to AC power supply thanks to integrated control gear

Product features

- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Uniform illumination
- Protection class: II
- High color consistency: ≤ 6 SDCM
- Lifetime (L70/B50): up to 20,000 h
- Type of protection: IP20
- Color rendering index R_a: > 80
- Mercury-free and RoHS compliant



© 2025, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data


Nominal wattage	6.50 W
Nominal voltage	220…240 V
Mains frequency	50…60 Hz
Power factor λ	0.50
Protection class	II

Photometrical data

Luminous flux	500 lm
Luminous efficacy	77 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥80
Beam angle	100 °

Dimensions & Weight

Diameter	118.00 mm
Height	52.00 mm
Product weight	100.00 g
Cable length	150 mm



LDVAL DL40 INCURV 6.5W

Materials & Colors

Product color	White
Housing color	White
Body material	Polybutylene terephthalate (PBT)
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

© 2025, LEDVANCE GmbH. All rights reserved.

Application & Mounting

Ambient temperature range	-20…+40 °C
Temperature range at storage	-20…+70 °C
Type of protection	IP20
Dimmable	No
Mounting type	Recessed
Mounting location	Ceiling
Application environment	Indoor
Mounting diameter	105.00 mm

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable

DOWNLOAD DATA

	Photometric and lighting design files	Document name
	IES file (IES)	LDVAL DL40 INCURV 6.5W

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075249561	Folding box 1	129 mm x 77 mm x 128 mm	552.00 g	1.27 dm^3
4058075249578	Shipping box 24	409 mm x 331 mm x 284 mm	14013.00 g	38.45 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2025, LEDVANCE GmbH. All rights reserved.